

Zephyr[®] Fume Arm



TECHNICAL DATA

Hanging Part #	Model	Diameter	Length	Hood Diameter	CFM
207870206	F0710	3 in	3 ft	4 in	60 - 200
207870207	F0715	3 in	5 ft	4 in	60 - 200
207870208	F1015	4 in	5 ft	8 in	100 - 350
207870210	F1025	4 in	8 ft	8 in	100 - 350
207870202	F1620	6 in	7 ft	12 in	450 - 850
207870203	F1630	6 in	10 ft	12 in	450 - 850
207870204	F1640	6 in	14 ft	12 in	450 - 850
207870211	F2020	8 in	7 ft	14 in	750 - 1200
207870212	F2030	8 in	10 ft	14 in	750 - 1200
207870213	F2040	8 in	14 ft	14 in	750 - 1200

Standing Part #	Model	Diameter	Length	Hood Diameter	CFM
207870006	F0710P	3 in	3 ft	6 in	60 - 200
207870007	F0715P	3 in	5 ft	6 in	60 - 200
207870008	F1015P	4 in	5 ft	8 in	100 - 350
207870002	F1620P	6 in	7 ft	12 in	450 - 850
207870003	F1630P	6 in	10 ft	12 in	450 - 850
207870011	F2020P	8 in	7 ft	14 in	750 - 1200
207870012	F2030P	8 in	10 ft	14 in	750 - 1200

THE ZEPHYR FUME ARM

The Zephyr Fume Arm is an easy to use extraction arm made for capturing welding fumes, soldering fumes, plasma cutting, grinding dusts, powders, and other situations where lots of fumes, sparks and spatter are generated. Its flexible joints make the hood easy to maneuver and locate in the right position.

FEATURES & BENEFITS

- Tube, 26-gauge, galvanized, powder coated
- Hood, aluminum, powder coated Yellow
- Wall Bracket, steel, powder coated Black
- Duct Connection Collar, steel
- External Aluminum Joints, powder coated Black
- Black Hose, rated for 275 Degree F
- Spring Shock Assembly, aluminum
- Shut off Damper, built into lower tube, steel, powder coated Black
- Grab Handle around the Hood, aluminum, powder coated Black



www.camfilapc.com